Chains . 0.80	A point 40.00 chs. in departure from the cor. of secs. 32 and 33.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 32 only, with brass cap mkd.
	½ S32
	1937
	of stone, 2 ft. base; $1\frac{1}{2}$ ft. high, N. of cor.
39•97	The point for cor. of secs. 5, 6, 31, and 32, which is mkd. by the original cor. stake, a redwood post 4 ins. square and 3 ft. long, mkd. as follows: T15NS32 on NE., R28ES5 on SE., T14NS6 on SW. and S31 on NW. faces.
	At point for cor.
	Set an iron post, 3 ft. long 2 ins. diam., 27 ins. in the ground, with the original cor. post deposited alongside, for cor. of secs. 5 and 6 only, with brass cap mkd.
	T15N R28E
	S32 S6 S5
	TIAN
8	1937 raise a mound
	of stone, 2 ft. base, 12 ft. high, S. of cor.
	Land, level valley floor. Soil, sandy, 3d rate. No timber; undergrowth, shadscale and button sage. Grazing, poor.
* 1	S. 89° 27' W., along N. bdy. of sec. 6, east half mile.
	Over nearly level valley floor, through medium dense undergrowth.
0.83	A point 80.00 chs. in departure from the cor. of secs. 32 and 33.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 31 and 32 only, with brass cap mkd.
	T15N R28E <u>S31 S32</u> S6 T14N
1 12	. 1937 .
10.80	Begin to asc. gentle E. slope.
18.30	Spur, slopes SW.
27.50	Wash, course SW.
39.96	The point for \$\frac{1}{4}\$ sec. cor. of secs. 5 and 6, which is mkd. by the original cor. stone, a lava rock \$x7x14 ins., mkd. with \$\frac{1}{4}\$ on N. face and mound of stone, 2 ft. base and \$l\frac{1}{2}\$ ft. high, N. of cor.
	At point for cor.
яз	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with original cor. stone deposited at the base, for 4 sec. cor. of sec. 6 only, with brass cap mkd.