

WEST BOUNDARY OF T. 15 N., R. 28 E.

Chains	
20.70	Ridge, bears W. and SE., desc. 230 ft. over N. slope.
26.00	Head of drain, course NW., continue to desc.
35.20	Knoll 2 chs. W. of line, desc. 30 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S1 S6 1937 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue over broken mountainous land, desc. 30 ft.
42.60	Wash, course NW.
44.40	Toe of spur, slopes from E.
45.30	Wash, course SW., asc. 240 ft. over broken SE. and SW. slopes.
57.00	Slope changes to SW., continue to asc.
67.80	East shoulder of peak, slopes S. 80° E.
70.40	Intersect Third Standard Parallel North,
	Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of Tp. 15 N., Rs. 27 and 28 E., with brass cap mkd.

T16N R27E
S36

S1 | S6
R27E | R28E

T15N
CC

1937

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

From the point of intersection, the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 36, T. 16 N., R. 27 E., bears E. 14.79 chs. dist., a 1 in. iron post firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group.

From this same point the standard sec. cor. of secs. 35 and 36, T. 16 N., R. 27 E., bears W. 25.21 chs. dist.; a 2 in. iron post, firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group.

Land, broken and mountainous.

Soil, rocky, 4th rate.

No timber; undergrowth, shadscale and rabbitbrush.

Grazing, fair.

SURVEY OF SUBDIVISIONS OF T. 15 N., R. 28 E.

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., hereinbefore described.

Thence

N. 0° 01' W., bet. secs. 35 and 36.