

SUBDIVISION OF T. 15 N., R. 28 E.

Chains	
	East, on random line, bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.00	Intersect E. bdy. of T _o . 4 lks. S. of cor. of secs. 19, 24, 25 and 30, a 2 in. iron post, firmly set, mkd. and witnessed as described in the field notes of T. 15 N., R. 29 E., book "T" executed under this group.
	Thence
	S. 89° 58' W., on true line, bet. secs. 24 and 25.
	Over rolling mountainous land through scattered undergrowth, desc. 440 ft. over N. and NW. slopes to $\frac{1}{4}$ sec. cor.
28.70	Slope changes to NW., continue to desc.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> S 24 $\frac{1}{4}$ S 25 1937 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Continue to desc. 50 ft. over N. and NW. slopes.
45.00	Slope changes to gentle W. slope, continue to desc.
51.30	Dirt road, bears N. 60° E. and S. 60° W., across level valley floor.
73.00	Dirt road, bears N. and S.
80.00	The cor. of secs. 23, 24, 25 and 26.
	Land, rolling and mountainous. Soil, sandy, 4th rate. No timber; undergrowth, shadscale and rabbitbrush. Grazing, poor.
	N. 0° 01' W., bet. secs. 23 and 24.
	Across rolling valley floor through scattered undergrowth.
11.50	Drain, course S. 30° E.
12.50	Dirt road, bears S. 30° E. and N. 30° W.
16.00	Begin to asc. along W. slope 60 ft.
28.80	Drift sand spur, slopes S. 60° W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S23 S24 </div>
	1937
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue over W. slope.
60.30	Asc. S. slope 70 ft.