

## SUBDIVISION OF T. 15 N., R. 28 E.

Chains	for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> <math>\frac{1}{4}</math>  S 4  S 9  1937 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Continue to asc. E. slope 20 ft.
42.80	Ridge, bears NE. and SW. 8 chs. to main ridge, continue to asc. 90 ft. over broken N. slope.
46.90	Head of draw, drains N. $30^{\circ}$ E.
60.00	Divide, bears S. $15^{\circ}$ E. and N. $15^{\circ}$ W., desc. over broken W. slope.
69.60	Draw, drains S. $10^{\circ}$ W., asc. 50 ft. along E. slope of flat top mountain.
80.06	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling mountains. Soil, sandy and rocky, 4th rate. No timber; undergrowth, shadscale and rabbitbrush. Grazing, poor.
	N. $0^{\circ} 03'$ W., bet. secs. 4 and 5.
	Over rolling flat top mountain through scattered undergrowth, asc. 50 ft. along S. slope.
5.70	Swale, extends S. $70^{\circ}$ E.
22.10	Summit of divide, bears NE. and SW., desc. 220 ft. along NW. slope.
38.20	Change to N. slope, continue to desc.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> <math>\frac{1}{4}</math>  S 5   S 4  1937 </div>
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	Continue to desc. 290 ft. over broken N. slope.
47.40	Sidehill drain, course N. $10^{\circ}$ E.
48.80	Toe of spur, slopes from N. $10^{\circ}$ E.
56.70	Wash, course N. $60^{\circ}$ E., asc. SE. slope 230 ft. to sec. cor.
71.09	Intersect Third Standard Parallel North.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 4 and 5, with brass cap mkd.
	<div style="text-align: center;"> T16N R28E  S32  S 5   S 4  T15N R28E  CC  1937 </div>