

## SUBDIVISION OF T. 15 N., R. 28 E.

Chains	Land, broken and mountainous. Soil, sandy and rocky, 4th rate. No timber; undergrowth, shadscale and rabbitbrush. Grazing, poor.
N. 0° 03' W., bet. secs. 5 and 6.	
Over mountainous land through scattered undergrowth, desc. 50 ft. over NE. slope.	
3.10 Wash, course NW., asc. 170 ft. over broken SE. slope.	
6.80 Wash, course NW.	
13.60 Hillside drain, course W.	
16.50 Slope changes to W., thence to NW., desc. 190 ft.	
20.60 Spur, slopes NW., 5 chs. to knoll.	
33.70 Wash, course W., asc. 80 ft. over S. slope.	
40.00 Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, with granite rock 5x6x8 ins., mkd. X, deposited at the base and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.	
$\frac{1}{4}$ S6   S5 1937	
Continue to asc. 50 ft. over S. slope.	
47.40 Ridge, bears E. and W., desc. 70 ft. over N. slope.	
54.30 Wash, course NW., asc. S. slope 150 ft.	
64.50 Shoulder of peak, slopes W. from peak 2 chs. E., desc. 120 ft. over N. slope to sec. cor.	
70.61 Intersect Third Standard Parallel North.	
Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.	
T16N R28E S31 S 6   S 5 T15N R28E CC 1937	
raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.	
From the point of intersection the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 16 N., R. 28 E., bears E. 18.43 chs. dist.; a 1 in. iron post firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group.	
From this same point the standard Tp. cor. of Tps. 16 N., Rs. 27 and 28 E., bears W. 21.57 chs. dist.; a 3 in. iron post firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group.	
Land, broken and mountainous. Soil, rocky, 4th rate. No timber; undergrowth, shadscale and rabbitbrush. Grazing, poor.	