EAST BOUNDARY OF T. 14 N., R. 29 E.

-		
	Chains	
	7.10 - 20	For description and tests of instruments used on the survey of this township, refer to the field notes of T. 13 N., R. 32 E., executed under this group. The azimuth for all lines was determined by transit angles turned from meridian stations which were established on the E., N. and W. bdys. of the township.
		Beginning at the corner of Tps. 13 and 14 N., Rs. 29 and 30 E.; a 3 in. iron post, mkd. and witnessed as described in the official record.
¥).		North, bet. secs. 31 and 36, over broken mountainous land, through medium dense undergrowth; asc. 60 ft. over broken S. slope.
	6.80	Low spur, slopes SE. 2 chs.; thence S.
	.14.80	Low spur, slopes S. 10° E.; from N. 20° W.; thence along SE. slope.
	30.30	Dry wash, course SE., heads 10 chs. NW.
	32.50	Point of low spur, slopes SE. 8 chs.
	38.50	Large draw, drains SE.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
		14
		s36 s31 1937
		of stone, 5 ft. base, 3 ft. high, W. of cor.
		This cor. is on N. edge of draw; continue to ascend broken S. slope 60 ft.
	52.70	Spur, slopes S. 30° E.; desc. N. slope.
	56.80	Head of small draw, drains S. 85° E.; asc. S. slope.
	59.30	Spur, slopes S. 70° E., 10 chs. to end; desc. NE. slope.
	68.10	Large draw, drains SE.; asc. broken SW. slope.
	74.50	Point of short spur, slopes SW. 5 chs.; desc. NW. slope, to cor.
	80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, with a lava rock, 6x6x8 ins., mkd. X, deposited at the base, for cor. of secs. 25, 30, 31 and 36, with brass cap mkd.
	* 17 17 17 17 17 17 17 17 17 17 17 17 17	T14N R29E R30E S25 S30 S36 S31
٠		1937 raise a mound
		of stone, 2 ft. base and $l_{\overline{z}}^{\frac{1}{2}}$ ft. high, W. of cor.
		Land, hilly, broken and mountainous. Soil, sandy in washes, coarse and rocky on slopes, 4th rate.
		No timber. Undergrowth, shadscale, sage and rabbit brush. Grazing, poor.
08 E7	MARKET CONTRACTOR OF THE PARTY	