

EAST BOUNDARY OF T. 15 N., R. 29 E.

Chains

T15N	
R29E	R30E
S1	S6

S12	S7

1937

raise a mound of stone, 2 ft. base and 1 1/2 ft. high, W. of cor.

From this cor. the cairn on a rocky peak bears S. 25° 01' W., 24.77 chs. distant.

Land, rolling. Soil, sandy and rocky, 4th rate. No timber. Undergrowth, shadscale, very sparse and scattered. Grazing, poor.

North, bet. secs. 1 and 6.

Over rolling mountainous land, through scattered undergrowth, asc. along general SW. slopes.

4.30 Draw, drains SW.

8.60 Spur, slopes S. 30° W., asc. 40 ft. along S. slope.

14.90 Sandy spur, slopes S. 70° W., continue to asc. 30 ft. along S. slope.

22.80 Top of sand ridge, bears E. and W., asc. S. slope 240 ft.

30.50 Base of mountains.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, and in a mound of stone to top; with rock 3x3x6 ins. mkd. X, deposited at base, for 1/4 sec. cor., with brass cap mkd.

S1	S6
----	----

1937

Continue over broken mountainous land, asc. along S. slope.

43.30 Spur, slopes W.

59.20 Draw, drains SW. from 10 chs. NE., asc. 110 ft. along S. slope.

63.30 Spur, slopes SW. 20 chs., continue to asc.

69.00 Main drainage divide, bears E. and W., begin to desc. along N. slope.

71.47 Intersect 3rd. Standard Parallel N.

Set an iron post, 3 ft. long, 3 ins. diam., 16 ins. in the ground, and in a mound of stone to top, for closing cor. of Tps. 15 N., Rs. 29 and 30 E., with brass cap mkd.

T16N	R29E

S1	S6

R29E	R30E
------	------

T15N

CC

1937

From the point of intersection the standard 1/4 sec. cor. S. bdy. of S. 36, T. 16 N., R. 29 E., bears E. 18.99 chs. dist., a 1 in.