

SUBDIVISIONS OF T. 15 N., R. 29 E.

| Chains | Thence | Series |
|--------|--|---------|
| 40.02 | <p>N. 89° 58' W. on true line, bet. secs. 3 and 10. Over gentle rolling sand hills, through scattered undergrowth. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with charcoal deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> | S3 |
| 80.04 | <p>1937 Continue over sandy rolling land. The cor. of secs. 3, 4, 9 and 10. Land, gentle rolling. Soil, sandy. No timber. Undergrowth, shadscale and greasewood. Grazing, poor.</p> | 1937 |
| 34.90 | <p>N. 0° 02' W., bet. secs. 3 and 4. Over rolling sand hills through medium dense undergrowth. Asc. gentle S. slope 60 ft. Slope changes to W. slope, continue to asc. 15 ft.</p> | 10.01 |
| 40.00 | <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with charcoal deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> | S4 S3 |
| 56.00 | <p>raise a mound of stone; 2 ft. base and $1\frac{1}{2}$ ft. high; W. of cor.</p> | 10.02 |
| 67.90 | <p>Contintae over rolling sand hills.</p> | 10.03 |
| 71.40 | <p>Swale, extends to SW., asc. S. slope 40 ft. Top of spur, slopes W. 4 chs. to end. Intersect Third Standard Parallel North. Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 3 and 4 with brass cap mkd.</p> | 10.04 |
| 80.08 | <p>T16N R29E S33 S4 S3 T15N R29E CC 1937 From the point of intersection the standard $\frac{1}{4}$ sec. cor., S. bdy. of sec. 33, T. 16 N., R. 29 E., bears E. 18.85 chs. dist.; a 1 in. iron post firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North</p> | 10.08 |