

## SUBDIVISIONS OF T. 15 N., R. 29 E.

Chains	
	asc. SW. slope 10 ft.
39.80	Spur, slopes S. 20° E., desc. 200 ft. over SW. slope.
55.20	Wash, course S. 5.00 chs., thence S. 40° E.
59.20	Wash, course N. S., from N.E. end, asc. 90 ft. over SW. slope.
79.19	The cor. of secs. 5, 6, 7 and 8. The land is rough and mountainous, rocky soil, with timber and brush, undergrowth, shadscale and mountain rush, grazing, very poor.
103.00	Canyon, bears S. 70° E., continues to desc. 150 ft. over NE. slope.
140.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 5 and 6, mkd. with brass cap.
160.00	Continue to desc. 240 ft. over rough broken NE. slope.
180.00	Ravine, course NE.
200.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
230.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
271.19	Intersect Third Standard Parallel North, T. 15 N., R. 29 E., at point of intersection of the boundaries of Secs. 5 and 6, mkd. with brass cap.
280.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
30.00	Spur ridge, bears SE. and NW., desc. along broken NE. slope.
38.10	Canyon, drains S. 70° E., continues to desc. 150 ft. over NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of secs. 5 and 6, mkd. with brass cap.
48.00	Continue to desc. 240 ft. over rough broken NE. slope.
50.20	Ravine, course NE.
54.90	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
67.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
71.19	Intersect Third Standard Parallel North, T. 15 N., R. 29 E., at point of intersection of the boundaries of Secs. 5 and 6, mkd. with brass cap.
78.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
80.00	Continue to desc. 240 ft. over rough broken NE. slope.
82.00	Ravine, course NE.
86.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
90.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
94.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
100.00	Continue to desc. 240 ft. over rough broken NE. slope.
104.00	Ravine, course NE.
108.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
112.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
116.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
124.00	Continue to desc. 240 ft. over rough broken NE. slope.
128.00	Ravine, course NE.
132.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
136.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
140.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
148.00	Continue to desc. 240 ft. over rough broken NE. slope.
152.00	Ravine, course NE.
156.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
160.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
164.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
172.00	Continue to desc. 240 ft. over rough broken NE. slope.
176.00	Ravine, course NE.
180.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
184.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
188.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
196.00	Continue to desc. 240 ft. over rough broken NE. slope.
200.00	Ravine, course NE.
204.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
208.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
212.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
220.00	Continue to desc. 240 ft. over rough broken NE. slope.
224.00	Ravine, course NE.
228.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
232.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
236.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
244.00	Continue to desc. 240 ft. over rough broken NE. slope.
248.00	Ravine, course NE.
252.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
256.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
260.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
268.00	Continue to desc. 240 ft. over rough broken NE. slope.
272.00	Ravine, course NE.
276.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.
280.00	Spur ridge, slopes E., from N. 10° W., desc. NE. slope.
284.00	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for closing cor. of secs. 5 and 6, mkd. with brass cap.
292.00	Continue to desc. 240 ft. over rough broken NE. slope.
296.00	Ravine, course NE.
300.00	Wash in canyon, course SE., asc. 260 ft. over SW. slope.