SECOND STANDARD PARALLEL NORTH, ALONG THE SOUTH BOUNDARY OF

T. 11 N., R. 30 E.

Chains	For description of instruments and method of measurement, refer to the field notes of T. 13 N., R. 32 E., executed under this group.
3 '	
i di prima ja	ESTABLISHMENT OF THE SECOND STD. PAR. N., ALONG THE SOUTH BDY. OF T. 11 N., R. 30 É.
	Beginning at the Std. cor. of Ts. 11 N., Rs. 30 and 31 E., which is an iron post, 3 ins. diam., firmly set, mkd., and witnessed as described in the field notes of T. 11 N., R. 31 E., executed under this group.
-8-0A	West, with the establishment of the second standard parallel north along the S. bdy. of Sec. 36, T. 11 N., R. 30 E., on a transit line describing the tangent which is obtained by deflection of 0° O4.1', checked by 6 repetitions to the north from the projected transit line initiated at the Std. cor. of Ts. 11 N., Rs. 31 and 32 E. The azimuth thus determined is further verified and found to be correct by a Polaris observation at the Std. 4 sec. cor. of Sec. 34.
	Over rolling mountainous land thru medium dense low undergrowth. Desc. a broken S. slope 60 ft.
13.70	Dry wash, 35 lks. wide, 1 ft. deep, course S. 10° W., asc. 70 ft. over a broken SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Std. \(\frac{1}{4} \) sec. cor., with brass cap mkd.
5 4 3 . 3 2	SC- \$\frac{1}{4}\$ S 36
	1937 raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
42.70	Draw, drains S. 65° E., asc. 80 ft. over NE. slope.
47.20	
51.40	Small draw, drains N., desc. along broken S. slope, 80 ft.
68.60	Dry wash, 60 lks. wide, 1 ft. deep, course S.
76.50	Top of small rocky knoll, bears N. and S.
80.00	N. 1 lk. from the tangent,
dar ora	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for std. cor. of secs. 35 and 36, with brass cap mkd.
•	SC TIIN R30E S35 S36
	1937 raise a mound
	of stone, 2 ft. base, 12 ft. high, N. of cor.
	Land, hilly. Soil, sandy to gravelly clay loam, 3rd rate. Undergrowth, shadscale, greasewood.