

## SECOND STD. PAR. N., ALONG S. BDY. OF T. 11 N., R. 30 E.

## Chains

No timber.

Grazing, fair to poor.

West, along the S. bdy. of Sec. 35, on a transit line describing the tangent which bears S.  $89^{\circ} 59.3'$  W.

Over broken hilly land thru scattering low undergrowth.

10.10 Low rocky knoll, bears N. and S.

14.20 Draw, drains NW.

25.00 End of spur from the S.

33.60 Recross draw, drains SW.

36.30 Spur, slopes S. 3 chs., thence W.

38.40 Head of small draw, drains S.  $80^{\circ}$  W.

40.00 N. 2 lks. from the tangent,

Set an iron post, 3 ft. 1 in. diam., 22 ins. to solid rock with a basalt rock, 5x3x2 ins., mkd. X, deposited at the base, and in a large mound of stone to top of post, for std.  $\frac{1}{4}$  sec. cor., with brass cap mkd.

SC

 $\frac{1}{4}$  S 35

1937

46.00 Recross small draw, drains N.  $80^{\circ}$  W., continue along broken N. slope.54.20 Spur, slopes S.  $70^{\circ}$  W. from S.  $80^{\circ}$  E., desc. 80 ft. over NW. slope.

60.20 Recross draw, drains S.

70.00 Head of draw, drains SW.

77.60 Small draw, drains S.  $80^{\circ}$  W.

80.00 N. 3 lks. from the tangent,

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd.

SC

T11N R30E

S34 | S35

1937

raise a mound  
of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, N. of cor.

Land, broken hilly.

Soil, shallow gravelly to rocky loam, 3rd rate.

Undergrowth, shadscale, greasewood.

No timber.

Grazing, poor.

West, along the S. bdy. of Sec. 34, on a transit line describing the tangent which bears S.  $89^{\circ} 58.6'$  W.

Over broken hilly land thru scattering low undergrowth.