

SECOND STD. PAR. N., ALONG S. BDY. OF T. 11 N., R. 30 E.

Chains

Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for standard cor. of T. 11 N., R. 30 E., only, with brass cap mkd.

SC

T11N

R30E

S31

1937

raise a mound
of stone, 3 ft. base, 2 ft. high, NE. of cor.

From this cor., the old Std. cor. of Ts. 11 N., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears North, 3.31 chs. distant.

As this cor. will hereafter refer only to R. 29 E., I alter the brass cap markings to read as follows:

SC

T11N

R29E

S 36

1937

raise a mound
of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, NW. of cor.

Land, broken mountainous to rolling.
Soil, coarse rocky to gravelly clay loam, 3rd rate.
Undergrowth, shadscale, greasewood.
No timber.
Grazing, fair.

SUBDIVISION OF T. 11 N., R. 30 E.

I commence the subdivisional survey at the std. cor. of secs. 35 and 36, hereinbefore described.

N. $0^{\circ} 01' W.$, bet. secs. 35 and 36,

Over broken hilly land thru medium dense low undergrowth.

23.40 Head of small draw, drains S. $30^{\circ} W.$

29.60 Spur, slopes SE.

39.80 Draw, drains SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

 $\frac{1}{4}$

S35

S36

1937

raise a mound
of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.

Asc. 70 ft. over S. slope.

49.60 Spur, slopes S. $60^{\circ} E.$