

327

## SUBDIVISION OF T. 11 N., R. 30 E.

Chains	
21.40	Spur, slopes S. 60° E., continue along S. slope.
29.90	Small spur, slopes S. from NE., desc. 80 ft. over broken W. slope.
38.70	Draw, drains SE.
39.96	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 2 $\frac{1}{4}$
	S 11
	1938
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Asc. 120 ft. over NE. slope.
50.00	End of spur from N. 60° W., desc. along broken S. slope.
69.10	Draw, drains S. 60° E., asc. 60 ft. over rolling E. slope.
79.92	The cor. of secs. 2, 3, 10, and 11.
	Land, rolling and hilly.
	Soil, shallow gravelly loam, 3rd rate.
	Undergrowth, shadscale, greasewood, rabbit brush.
	No timber.
	Grazing, fair to good.
	N. 0° 01' W., on true line bet. secs. 2 and 3,
	Over rolling land thru medium dense low undergrowth.
16.00	Spurs, slope S. 70° E. and N. 60° E.
26.40	Draw, drains N. 60° E.
26.80	Wire fence, 4 strand barbed, bears E. and W.
26.96	Intersect N. bdy. of Tp. at a point from which the cor. of Ts. 12 N., Rs. 30 and 31 E., an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East 16.86 chs. distant.
	At point of intersection.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.
	T12N R30E
	S 36
	S3   S2
	T11N R30E
	CC
	1938
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.
	Land, rolling.
	Soil, gravelly to rocky loam, 3rd rate.
	Undergrowth, shadscale, greasewood.
	No timber.
	Grazing, fair.