

SUBDIVISION OF T. 11 N., R. 30 E.

Chains	
4.00	Spur, slopes S. 10° W., continue along broken W. slope.
13.70	Spur, slopes S. 50° W. from E., desc. 50 ft. over abrupt N. slope.
17.40	Draw, drains W., asc. 70 ft. to cor. over broken SW. slope.
23.00	Small draw, drains SW.
27.16	Intersect the N. bdy. of Tp. at a point from which the cor. of secs. 35 and 36, T. 12 N., R. 30 E., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East 16.94 chs. distant.
	At point of intersection,
	Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground to underlying rock, over a cross X, cut at exact cor. point, and in a large mound of stone to top of post, for closing cor. of secs. 3 and 4, with brass cap mkd.
	<div style="text-align: center;"> T12N R30E S35 ————— S4 S3 T11N R30E CC 1938 </div>
	Land, mountainous. Soil, shallow rocky loam, 3rd rate. Undergrowth, shadscale, greasewood. No timber. Grazing, poor.
	From the Std. cor. of secs; 32 and 33 on the S. bdy. of the Tp.,
	N. 0° 03' W., bet. secs. 32 and 33,
	Over broken mountainous land thru scattering low undergrowth. Desc. 210 ft. over a broken N. slope.
19.60	Draw, drains N. 30° E., asc. 60 ft. over rocky SW. slope.
22.30	Small rocky spur, slopes N. 30° E., desc. along W. side of top.
32.00	Recross same spur, slopes NW., desc. 90 ft. over NE. slope.
36.70	Draw, drains N. 20° W., continue along W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S32 S33 1938 </div>
	<div style="text-align: right;">raise a mound</div> of stone, 2 ft. base, 1½ ft. high, W. of cor.
	Asc. 80 ft. over rocky S. slope.