

345

SUBDIVISION OF T. 11 N., R. 30 E.

Chains	
	N. 0° 03' W., on true line bet. secs. 4 and 5. Over broken hilly land thru scattering low undergrowth.
1.90	Head of draw, drains E., asc. 60 ft. over rocky S. slope.
5.00	Spur, slopes E. 4 chs., desc. along steep E. slope.
6.30	Small drain, course E.
11.20	End of rocky spur from W., desc. 150 ft. over steep NE. slope.
17.80	Draw, drains NW.
18.00	Old road, bears NW. and SE., continue over rolling W. slope thru medium dense undergrowth.
27.11	Intersect N. bdy. of Tp., at a point from which the cor. of secs. 34 and 35, T. 12 N., R. 30 E., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East 16.68 chs. distant. At point of intersection. Set an iron post, 3 ft. long, 2 ins. diam., 22 ins. in the ground, to underlying rock, and in a large mound of stone to top of post, for closing cor. of secs. 4 and 5, with brass cap mkd.
	T12N R30E S 34 ----- S5 S4 T11N R30E CC 1938
	Land, hilly and rolling. Soil, shallow gravelly to rocky loam, 3rd rate. Undergrowth, shadscale, greasewood, rabbit brush. No timber. Grazing, fair.
	From the Std. cor. of secs. 31 and 32 on the S. bdy. of the Tp., N. 0° 03' W., bet. secs. 31 and 32. Over rough mountainous land thru scattering low undergrowth. Asc. 120 ft. over abrupt, rocky S. slope.
5.10	Spur, slopes W., desc. 310 ft. over broken N. slope.
25.20	Draw, drains N. 80° W., asc. 280 ft. over steep, rocky S. slope.
35.70	Spur, slopes S. 60° W., 2 chs., thence W., continue along W. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock, with a basalt rock, 8x4x4 ins., mkd. X, deposited at the base, and in a large mound of stone to top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S31 S32 1937