12-13-m

	Chains	
	•	s 7
		La el la company de la company
	To the said	s 18 1938
		Continue along very rough and broken N. slopes.
	52.60	Spur, slopes N. 30°.E.
	63.10	Rocky draw, drains N. 10° W.
	73.50	Spur, slopes N. 30° W., desc. 140 ft. over abrupt, rocky W. slope.
	77.30	Rocky ravine, drains NW.
	80.00	In rocky ravine draining N.
		Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground over a cross X, cut at exact cor. point on solid granite ledge, and in a large mound of stone, 6 ft. base, for cor. of lots 7 and 8 in Sec. 7 and lots 1 and 2 in Sec. 18, with brass cap mkd.
	ection in the	S 7
		2 1 \$ 18
		1938
		Asc. 70 ft. over rocky NE. slope.
	83.70	Crest of sharp rocky spur, slopes N. 10° W. 3 chs. thence NW., desc. steep, rocky NW. slope, 390 ft. to W. bdy.
	92.10	Rocky draw, drains NW.
	94.40	Rocky draw, drains NW. Spur, slopes NW.
	100.86	Intersect W. bdy. of Tp.
		Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to underlying rock, with a basalt rock, 6x x ins., mkd. X, deposited at the base, and in a supporting mound of stone to top of post, for closing cor. of secs. 7 and 18, with brass cap mkd.
		. Tlln
	FE .235 W	R29E S 7
	× - 1-	S 13CC
S. James		s 18 1938
A CONTRACTOR OF THE PROPERTY O		From point of intersection the old cor. of secs. 7, 12, 13, and 18, T. 11 N., Rs. 29 and 30 E., bears N. 4.11 chs. dist., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record. As this cor. will hereafter refer only to R. 29 E., I alter the brass cap markings to read as follows: