ESTABLISHMENT OF \(\frac{1}{4} \) SEC. CORS. ALONG N. & W. BDYS. T. 11 N., R. 30 E.

Chains

terminate in

* 12 Per

5 4 s 6 1938

Deposit a basalt rock, 6x4x3 ins., mkd. X, at base of post.

½ Sec. cor. on W. bdy. of Sec. 31.

At a point mid-distant between the Std. cor. of T. 11 N., R. 30 E., and the closing cor. of secs. 30 and 31, and from which point the old \(\frac{1}{4} \) sec. cor. of secs. 31 and 36, now altered to refer to Sec. 36 only, bears N. 3.33 chs. dist.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for \(\frac{1}{4} \) sec. cor. of sec. 31 only, with brass cap mkd.

| ¹/₄ | s 31

½ Sec. Cor. on W. bdy. of Sec. 30.

At a point mid-distant between the closing cor. of secs. 30 and 31, and the closing cor. of secs. 19 and 30, and from which point the old $\frac{1}{4}$ sec. cor. of secs. 25 and 30, now altered to refer to Sec. 25 only, bears N. 3.41 chs., dist.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 30 only, with brass cap mkd.

\$ 30 1938

Deposit charcoal at base of post.

\$ Sec. Cor. on W. bdy. of Sec. 19.

At a point mid-distant between the closing cor. of secs. 19 and 30, and the closing cor. of secs. 18 and 19, and from which point the old $\frac{1}{4}$ sec. cor. of secs. 19 and 24, now altered to refer to Sec. 24 only, bears N. 3.66 chs. dist.

Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the ground over a cross X, cut at exact cor. point on solid rock, and in a large mound of stone, $5\frac{1}{2}$ ft. base, to top of post, for $\frac{1}{2}$ sec. cor. of sec. 19 only, with brass cap mkd.

s 19