		SURVEY OF THE SOUTH BOUNDARY OF T. 12 N., R. 30 E.
	Chains 16.30	Spur, projects N. 20° W. from S. about 1 ch., thence from E.; continue ascent along steep N. slope.
	28.30	End of ascent, bears N. and S.; desc. 190 ft. along a steep broken N. slope.
	37.60	Steep rocky draw, drains N. 20° E. to main canyon; asc. 160 ft. along a steep rocky NW. slope to the 53.20 ch. pt.
	40.00-	N., 2 lks. from the tangent,
		Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, to solid rock and in a mound of stone, 5 ft. base to top of post, for \$\frac{1}{2}\$ sec. cor. of sec. 32 only, T. 12 N., R. 30 E., with brass cap mkd.
		1936 · · ·
	42 .2 5	Fall 2 lks. S. of the cor. of Tps. 11 N., Rs. 29 and 30 E., which is an iron post, 3 ins. diam., firmly set, properly mkd. and witnessed, as described in the official record.
	53.20	Ridge, bears NE. from S. 60° W.; desc. 105 ft. over a gentle E. slope.
-	61.30	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° E.; asc. 15 ft. over a gentle W. slope.
	63.60	W. edge of draw, bears N. 10° W. and S. 10° E. about 2 chs., thence S. 80° E.; desc. 50 ft. over ledge facing E.
-	65.50	Center of draw, drains N. 10° W. from SE. 1 ch., thence from S. 80° E.; asc. 50 ft. over ledge facing W.
	67.40	E. edge of draw, bears N. and S. 80° E.; asc. 140 ft. over a W. slope.
-	80.00	N., 3 lks. from the tangent,
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 32 and 33, T. 12 N., R. 30 E., with brass cap mkd.
		T12NR30E \$32 \$33
		T11N 1936
		Deposit broken glass at base of post.
	8 (1)	This cor. is situated on the E. edge of a wash, 10 lks. wide, 1 ft. deep, draining NW. from S. 80° E.
		Land, rough mountainous. Soil, rocky; 4th rate.
	,	Undergrowth, greasewood and shadscale. Timber, none.
•		Grazing, fair.
		along the S. bdy. of sec. 33 East,/on a tangent line, which bears S. 89°58.6' E.
2	e deri-t	Over rough mountainous land, through medium dense under-