

SURVEY OF THE SOUTH BOUNDARY OF T. 12 N., R. 30 E.

Chains	
79.00	E. edge of head of canyon, bears N. and SW.; asc. gentle W. slope.
80.00	N. 29 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, for the cor. of Tps. 12 N., Rs. 30 and 31 E., with brass cap mkd.
	<div style="text-align: center;"> WRIR T12N R30E R31E S36 S31 T11N 1936 </div> <p style="text-align: right;">raise a mound</p> <p>of stone, 4 ft. base, 3½ ft. high, N. of cor.</p> <p>This cor. is situated about 1 ch. N. of a low bench, bearing E. and W., which is the main divide between drainages N. and SE.</p> <p>Land, rolling mountainous. Soil, shallow and rocky; 3rd rate. Undergrowth, greasewood and shadscale. Timber, none. Grazing, poor on steep rocky slopes; fair to good in other areas.</p>

SURVEY OF A PORTION OF THE SUBDIVISION
OF T. 12 N., R. 30 E.

	Commence the subdivisional survey at the cor. of secs. 33 and 34, on the S. bdy. of the Tp., heretofore described.
	N. 0°02' W., bet. secs. 33 and 34.
	Over mountainous land, through medium dense undergrowth; desc. 125 ft. to the 39.00 ch. pt.; desc. along a draw draining NW.
3.70	Dim road, bears N. 20° E. about 2 chs., thence N. from S. 30° W. along bottom of wash, draining N. 20° E.; continue along E. slope.
16.00	Same road and wash as at 3.70 ch. pt., bears N. 10° W.; desc. along general NW. slope.
28.80	Low spur, projects N. 70° W.
35.40	Dim road, in bottom of main wash, draining N. 70° W., bears N. 70° W. and S. 70° E.; continue along gentle W. slope.
39.00	Base of S. slope, bears NW. and SE.; asc. 20 ft. to the 41.10 ch. pt.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground and in a mound of stone, 4 ft. base to top of post, for ¼ sec. cor., with brass cap mkd.

¼ W
 R
 S33 | S34I
 1936 R