

.SUBDIVISION OF T. 14 N., R. 30 E.

Chains	
27.70	Road and wash, course S. 30° E. Road also bears N. 44½° W., asc. 40 ft. over NE. slope.
39.96	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd. S 29 ¼ ——— S 32 1937 Asc. an easterly slope 160 ft.
48.00	Spur, slopes S. 10° E. from peak 1 ch. N., desc. 50 ft. over SW. slope.
54.50	Wash, course SE.
67.00	Drain, course N. 80° E., from SW., asc. SE. slope 130 ft.
73.70	Slope changes to NE., continue to asc. 70 ft.
76.30	Slope changes to E., continue to asc. 70 ft. to cor.
79.92	The cor. of secs. 29, 30, 31, and 32. Land, rolling mountains. Soil, rocky, 4th rate. No timber; undergrowth, shadscale and rabbit brush. Grazing, poor.
40.00	S. 89° 56' W. on random line, bet. secs. 30 and 31. Set temp. ¼ sec. cor.
77.82	Intersect W. bdy. of Tp. 33 lks. S. of cor. of secs. 25, 30, 31, and 36, an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of T. 14 N., R. 29 E., executed under this group. Thence S. 89° 50' E. on true line, bet. secs. 30 and 31. Over mountainous land through medium dense undergrowth, asc. 190 ft. over NW. slope.
7.50	Spur, slopes SW., desc. 40 ft. over a broken SE. slope.
13.70	Minor spur, slopes SE. 4 chs.
20.40	Draw, drains S. 10° E., asc. 250 ft. over SW. slope.
37.82	Set an iron post, 3 ft. long, 1 in. diam., over a X on solid rock against a rock ledge and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd. S 30 ¼ ——— S 31 1937 Continue to asc. 260 ft. over a steep rocky SW. slope.