

## SURVEY OF THE EAST BOUNDARY OF T. 15 N., R. 30 E.

Chains

$$\frac{1}{4}$$

S12	S7
-----	----

1937

raise a mound

of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, W. of cor.

Continue over a gentle rolling westerly slope.

68.90

Wash, course NW.

78.20

Gully, course SW. to junction; asc. a gentle W. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, with a lava rock  $2\frac{1}{2} \times 6$  ins., mkd. X, deposited at the base and in a mound of stone to top, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd.

$$\frac{1}{4}$$

T15N	
R30E	R31E
S1	S6
S12	S7

1937

Land, rolling mountainous.

Soil, rocky and gravelly; 4th rate.

No timber; undergrowth, shadscale, greasewood, sagebrush and grass. Grazing, fair.

North, bet. secs. 1 and 6:

Over rolling land through medium dense undergrowth; asc. along a gentle southwesterly slope.

20.20

Wash, course W.

39.70

W. tip of small spur from E.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with a lava rock  $3\frac{1}{4} \times 6$  ins., mkd. X, deposited at the base and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\frac{1}{4}$$

S1	S6
----	----

1937

45.30

Draw, drains S.  $80^\circ$  W.; asc. along a gentle rolling SW. slope.

54.20

Slope changes to SW.

71.00

Main wash, course S.  $80^\circ$  W.; asc. 50 ft. over SW. slope.

72.23

Intersect the Third Standard Parallel North.

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground to solid rock and in a mound of stone to top, for closing cor. of Tp. 15 N., Rs. 30 and 31 E., with brass cap mkd.

$$\frac{1}{4}$$

T16N R30E	
S36	
S1	S6
R30E	R31E
T15N	
CC	

1937