

SUBDIVISION OF T. 15 N., R. 30 E.


Chains

N. 0° 01' W., bet. secs. 2 and 3.

Over rolling sandhills through scattered undergrowth; desc. 170 ft. over rolling NW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with charcoal deposited at the base, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.



Continue to desc. 30 ft. over NW. slope.

54.10

Sandy swale, drains NE.; asc. 200 ft. over rolling SE. slope.


70.80

Long sandy hill, bears E. and W.; desc. 40 ft. over N. slope.

72.02

Intersect the Third Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with charcoal deposited at the base for closing cor. of secs. 2 and 3, with brass cap mkd.



From the point of intersection the standard cor. of secs. 33 and 34, T. 16 N., R. 30 E., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the Third Standard Parallel North, executed under this group, bears West 16.88 chs. dist.

Land, rolling sand hills.  
Soil, fine drifted sand; 4th rate.  
No timber; undergrowth, shadscale, mountain rush and sage.  
Grazing, poor.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of T. 14 N., R. 30 E., executed under this group,

Thence

N. 0° 02' W., bet. secs. 33 and 34.

Over rolling land through medium dense undergrowth.

25.00

Unimproved road, bears SW. and NE.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a rock 3x5x6 ins., mkd. X, deposited at the base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

