

503

SUBDIVISION OF T. 15 N., R. 30 E.

Chains

with charcoal deposited at base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S4 \quad | \quad S3 \\ 1937 \end{array}$$

Continue to desc. 120 ft. along top of ridge bearing N.

58.40

Leave ridge, bears N. 30° E. and S.; desc. 110 ft. over NW. slope.

72.02

Intersect the Third Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with charcoal deposited at the base, for closing cor. of secs. 3 and 4, with brass cap mkd.

$$\begin{array}{c} T16N \quad R30E \\ S33 \\ \hline S4 \quad | \quad S3 \\ T15N \quad R30E \\ CC \\ 1937 \end{array}$$

From point of intersection the standard cor. of secs. 32 and 33, T. 16 N., R. 30 E., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of Resurvey of the Third Standard Parallel North, executed under this group, bears West 17.04 chs. dist.

Land, rolling sandy slopes.
Soil, fine sand; 4th rate.
No timber; undergrowth, shadscale, greasewood and rabbit brush.
Grazing, fair.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the survey of T. 14 N., R. 30 E., executed under this group.

Thence

N. 0° 03' W., bet. secs. 32 and 33.

Across a sandy flat through scattered undergrowth; asc. a very gentle SW. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a rock 3x4x5 ins., mkd. X, deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S32 \quad | \quad S33 \\ 1937 \end{array}$$

Continue across nearly level sandy flat.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a rock 3x5x6 ins., mkd. X, deposited at the base, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.