

SUBDIVISION OF T. 15 N., R. 30 E.

Chains

40.09 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a rock 4x4x5 ins., mkd. X, deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 4
 $\frac{1}{4}$
 S 9
 1937

Asc. 30 ft. over an E. slope.

44.30 Spur, slopes N.; desc. 20 ft. over W. slope.

61.60 Slope changes, asc. 40 ft. over an easterly slope.

80.18 The cor. of secs. 4, 5, 8 and 9.

Land, rolling.
 Soil, sandy; 3rd rate.
 No timber; undergrowth, shadscale and mountain rush.
 Grazing, poor.

N. 0° 03' W., bet. secs. 4 and 5.

Over rolling land through scattered undergrowth; desc. over a rolling NE. slope.

7.00 Shallow draw, drains N. 60° E.

37.50 Head of draw, drains NE.; asc. SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground with charcoal deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S5 | S4
 1937

Continue to asc. 70 ft. over SE. slope.

63.00 Spur, slopes E.; desc. 40 ft. over NE. slope.

71.80 Intersect the Third Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with charcoal deposited at the base, for closing cor. of secs. 4 and 5, with brass cap mkd.

T16N R30E
 S32
 S5 | S4
 T15N R30E
 CC
 1937

From the point of intersection the standard cor. of secs. 31 and 32, T. 16 N., R. 30 E., which is an iron post, 3 ft. long, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group, bears West, 16.86 chs. dist.

Land, rolling.
 Soil, sandy; 3d rate.
 No timber; undergrowth, shadscale and greasewood.
 Grazing, poor.