

Chains  
46.10

Divide, bears E. and W.; desc. 440 ft. over a N. slope.

71.70

Intersect the Third Standard Parallel North.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with charcoal deposited at the base, for closing cor. of secs. 5 and 6, with brass cap mkd.

T16N	R30E
S31	
-----	
S6	S5
T15N	R30E
CC	
1937	

From the point of intersection the standard cor. of Tps. 16 N., Rs. 29 and 30 E., which is an iron post, 3 ft. long, 3 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the resurvey of the Third Standard Parallel North, executed under this group, bears W. 17.06 chs. dist.

Land, rolling mountainous.

Soil, sandy and rocky; 4th rate.

No timber; undergrowth, shadscale and greasewood.

Grazing, poor.

---

ESTABLISHMENT OF  $\frac{1}{4}$  SEC. COR. ALONG THE N. BDY.  
OF T. 15 N., R. 30 E.

---

At midpoint on the N. bdy. of sec. 1.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, supported in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

-----
$\frac{1}{4}$ S 1

1937

from which

The standard  $\frac{1}{4}$  sec. cor. of sec. 35, T. 16 N., R. 30 E., bears W. 16.91 chs. dist.; an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

At midpoint on the N. bdy. of sec. 2.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with charcoal deposited at the base, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

-----
$\frac{1}{4}$ S 2

1937

from which

The standard  $\frac{1}{4}$  sec. cor. of sec. 34, T. 16 N., R. 30 E., bears W. 16.94 chs. dist.; an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.

At midpoint on the N. bdy. of sec. 3.

Set an iron post, 3 ft. long, 18 ins. in the ground to solid rock and in a mound of stone to top, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.