SUBDIVISION OF T. 11 N., R. 31 E.

Chains Draw, drains N. 40° E., continue along broken E. slope. 11.90. Intersect the N. bdy. of the Tp. at a point from which the cor. of secs. 35 and 36, T. 12 N., R. 31 E., an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East 17.62 chs. 26.84 distant. At point of intersection, Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 3 and 4, with brass cap mkd. T12N R31E S35 S4 S3 TIIN'R31E CC 1938 raise a mound of stone, 3 ft. base, 12 ft. high, S. of cor. Land, rolling and hilly. Soil, gravelly clay loam, 3rd rate. Undergrowth, shadscale, greasewood. No timber. Grazing, fair. From the Std. cor. of secs. 32 and 33 on the S. bdy. of the Tp., N.0°03'W., bet. secs. 32 and 33. Over rolling land thru medium dense low undergrowth, asc. over a gradual SE. slope, 100 ft. to 4 sec. cor. Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \(\frac{1}{4} \) sec. cor., with brass cap mkd. 40.00 S32 S33 1938 raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Dry wash, 15 1ks. wide, 1 ft. deep, course S. 30° E. 42.10 Recross same wash, course S. 10° W. 58.20 Recross same wash, drains S. 20° E. from N.70°W., asc. 62.80 170 ft. over broken S. slope. Spur, slopes SE., desc. 30 ft. over rocky NE. slope. 77.40 Set an iron post, 3 ft. long, 2 ins. diam., over a cross X, cut at exact cor. point on exposed ledge, and in a mound of stone, 8 ft. base to top of post, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd. 80.00 TIIN R31E S29|S28 S32 S33 1938 Land, S. 3/4 mile, rolling; balance, hilly. Soil, gravelly to coarse rocky loam, 3rd rate.