

73

SURVEY OF THE S. BDY. OF T. 12 N., R. 31 E.

Commence the survey of the S. bdy. of T. 12 N., R. 31 E. at the cor. of Tps. 12 N., Rs. 30 and 31 E., which is an iron post, 3 ins. diam., firmly set, properly mkd. and witnessed, as described in the official record.

Thence,

East along the S. bdy. of sec. 31, on a transit line, describing the secant, which starts at a point 4 lks. S. of the Tp. cor. and bears N. 89°57.9' E.

Over mountainous land, through medium dense undergrowth; asc. 200 ft. over a NW. slope to the 18.10 ch. pt.

- 2.80 Shallow wash, drains S. 60° W. about 3 chs., thence SE.
 7.40 NW. slope becomes abrupt.
 18.10 Spur, projects S. 30° W.; continue along flat top of spur.
 21.80 Edge of spur, bears NW. and SE.; desc. 340 ft. over a NE. slope to the 50.60 ch. pt.
 38.00 Slope becomes abrupt.
 40.00 North, 2 lks. from the secant;

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. sec. 31 only, with brass cap mkd.

WRIR

$\frac{1}{4}$ S31

1936

raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

- 50.60 Junction of draws draining SE. from NW. and NE.; asc. 230 ft. to the 68.10 ch. pt.; asc. along gentle W. slope.
 53.00 Base of steep rocky SW. slope, bears N. and S.; asc.
 68.10 Spur, projects S.; desc. 200 ft. over an E. slope to the sec. cor.
 80.00 On the secant,

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base to top of post, for cor. of secs. 31 and 32, T. 12 N., R. 31 E., with brass cap mkd.

WRIR

T12NR31E

S31 | S32

T11N

1936

This cor. is situated on the W. edge of a shallow wash, draining NE.

Land, mountainous.
 Soil, sandy to rocky; 3rd rate.
 Undergrowth, shadscale and greasewood.
 Timber, none.
 Grazing, fair.