

SURVEY OF THE S. BDY. OF T. 12 N., R. 31 E.

Chains	
	East, along the S. bdy. of sec. 32, on a transit line describing the secant, which bears N. 89°58.6' E.
	Over mountainous land, through medium dense undergrowth; asc. 15 ft. along N. slope of low spur, projecting E. about 3 chs. S. of line.
4.40	Top of ascent, bears N. and S.; desc. 90 ft. over a NE. slope.
9.40	Draw, drains S. 25° E.; asc. 185 ft. to the 29.20 ch. pt.; asc. along steep SW. slope.
11.20	Pt. of spur, projecting from N.; asc. along steep rocky W. slope.
14.20	Draw, drains S.
29.20	Spur, projects S.; desc. 420 ft. to the 44.80 ch. pt.; desc. along E. slope of spur, projecting E.
33.40	Slope changes to NE.
38.60	Slope changes to E.
40.00	South, 1 lk. from the secant, Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) cut in solid rock, and in a mound of stone, 7 ft. base to top of post, for $\frac{1}{4}$ sec. cor. of sec. 32 only, with brass cap mkd. WRIR <u>$\frac{1}{4}$ S32</u> 1936
44.80	Low saddle in spur, bears E. and W.; asc. 30 ft. along gentle W. slope of spur.
48.20	Spur, projects N. 10° E. and S. 80° E. from W.; desc. 200 ft. over a broken NE. slope.
57.90	W. edge of broad valley, bears N. and S.; continue along gentle N. slope of valley floor.
75.00	Wash, drains N.
80.00	South, 2 lks. from the secant, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 32 and 33, T. 12 N., R. 31 E., with brass cap mkd. WRIR T12NR31E <u>S32 S33</u> T11N 1936 Deposit an igneous rock, 3x5x6 ins., mkd. with a cross (X), at base of post. Land, W. 60 chs., mountainous; balance, rolling. Soil, shallow to rocky; 3rd rate. Undergrowth, shadscale and greasewood. Timber, none. Grazing, fair.