

## SURVEY OF THE S. BDY. OF T. 12 N., R. 31 E.

Chains Set an iron post, 3 ft. long, 2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base to top of post, for cor. of secs. 35 and 36, T. 12 N., R. 31 E., with brass cap mkd.

T12NR31E  
S35 | S36

T11N  
1936

Land,  $W\frac{1}{2}$  mile rough,  $E\frac{1}{2}$  mile rolling.  
Soil, rocky; 3rd rate.  
Undergrowth, shadscale and greasewood.  
Timber, none.  
Grazing, fair.

East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.  $89^{\circ}58.6'$  E.

Over rolling land, through medium dense undergrowth.

22.40 Wash, drains N.  $10^{\circ}$  E.

28.90 Wash, drains N.  $10^{\circ}$  E.

33.60 Wash, 30 lks. wide, 3 ft. deep, drains N.

40.00 North, 2 lks. from the secant,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{2}$  sec. cor. sec. 36 only, with brass cap mkd.

$\frac{1}{2}$  S36

1936

raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

45.00 Wash, 30 lks. wide, 2 ft. deep, drains N.  $20^{\circ}$  W.

51.30 Wash, 20 lks. wide, 3 ft. deep, drains N.  $30^{\circ}$  E.

59.60 Wash, 10 lks. wide, 2 ft. deep, drains NW.

62.20 Base of mountain, bears NW. and SE.; asc. 190 ft. over a SW. slope.

74.60 Spur, projects S.; desc. 10 ft. over a SE. slope.

75.70 Draw, drains S.  $20^{\circ}$  W.; asc. 85 ft. to the Tp. cor.; asc. over steep SW. slope.

78.00 Head of draw, drains S.  $80^{\circ}$  W.; asc. over steep rocky SW. slope.

80.00 North, 4 lks. from the secant,

Set an iron post, 3 ft. long, 3 ins. diam., over a cross (X) on solid rock, and in a mound of stone, 6 ft. base to top of post, for cor. of Tps. 12 N., Rs. 31 and  $31\frac{1}{2}$  E., with brass cap mkd.

T12N  
R31E | R31 $\frac{1}{2}$ E  
S36 | S35

T11N  
1936