

RANGE LINE THROUGH T. 12 N., BETWEEN RANGES 31 & 31½ E.

Chains 68.70	Spur, projects N. 30° W. from main spur projecting S. 60° W.; desc. over broken N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd. <div style="text-align: center;"> T12N R31E R31½E S1 S2 ────┬─── S12 S11 1936 </div> <p style="text-align: center;">Deposit charcoal at base of post.</p> <p>Land, mountainous. Soil, rocky; 4th rate. Undergrowth, greasewood and shadscale. Timber, none. Grazing, fair.</p>
	North, along the E. bdy. of T. 12 N., R. 31 E., bet. secs. 1 and 2. Desc. 40 ft. over a N. slope to the 13.90 ch. pt.
3.50	Wash, drains N. 70° W.
7.90	Wash, drains N. 75° W.
13.90	Wash, drains N. 80° W.; asc. 265 ft. to the 44.80 ch. pt.; asc. over rocky SW. slope.
25.10	Slope changes to S.; continue over numerous shallow draws and low rolling spurs.
30.10	Wash, drains N. 30° W.
40.00	True pt. for ¼ sec. cor. falls on sloping bedrock where it is impossible to establish a cor. monument.
40.55	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to solid rock and in a mound of stone, 6 ft. base, to top of post, for witness ¼ sec. cor., with brass cap mkd. <div style="text-align: center;"> ¼ S1 S2 WC 1936 </div>
44.80	Spur, projects W.; desc. 50 ft. over a N. slope.
49.90	Draw, drains W.; asc. 25 ft. over a S. slope.
52.90	Spur, projects W.; desc. 100 ft. over a broken N. slope.
62.40	Wash, drains W.; asc. 10 ft. over a S. slope.
65.90	Low spur, projects W. about 2 chs. to end; desc. 25 ft. over a NW. slope.
67.10	Draw, drains S. 70° W.; asc. 280 ft. over a steep rocky SE. slope.