

T. 15 N., R. 31 E.

Chains

For description of instruments and azimuth determinations, refer to the field notes of T. 15 N., R. 30 E., surveyed during the same period; under this group.

SUBDIVISION OF A PORTION OF T. 15 N., R. 31 E.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the N. bdy. of T. 14 N., R. 31 E., executed under this group.

N. 0° 03' W., bet. secs. 32 and 33,

Over rolling mountainous land thru medium dense undergrowth.

Desc. 30 ft. along broken E. slope of spur.

4.10 Spur, projects S. 10° W. from low saddle to the east.

Desc. 60 ft. over NW. slope.

9.20 Draw, drains S. 60° W., asc. 90 ft. over broken SW. slope.

21.70 Low rocky bluff on ridge bearing E. and W., desc. 30 ft. along N. slope.

25.30 Draw, drains S. 60° W., asc. 50 ft. over short S. slope.

33.60 Spur, slopes SW. from E., desc. along W. slope.

40.00 In head of draw draining SW.,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground over a cross X and in a large supporting mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S32 | S33
1937

Asc. 50 ft. over S. slope.

42.80 Spur, slopes N. 70° W. desc. 110 ft. along abrupt N. slope.

46.00 Draw, drains N. 70° W., asc. 130 ft. over SW. slope.

52.70 Point of rocky spur from the E., desc. 110 ft. along broken W. slope.

67.90 Draw, drains SW., asc. 60 ft. over rolling S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 28, 29, 32 and 33, with brass cap mkd.

T15N R31E
S29 | S28
S32 | S33
1937

of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of cor. raise a mound

Land, rolling to broken mountainous.
Soil, rocky coarse loam, 3d and 4th rate.