

SUBDIVISION OF T. 13 N., R. 31½ E.

Chains	INSTRUMENTAL DATA
	For description of instruments, determination of azimuth, and other instrumental data for the surveys in T. 13 N., R. 31½ E., refer to the official field notes of T. 13 N., R. 32 E. and T. 12 N., R. 31½ E., surveyed under this group.
	I commence the subdivision surveys at the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., which is an iron post, 2 ins. diam., mkd. and witnessed as described in the official record, field notes of T. 12 N., R. 31½ E., surveyed under this group.
	N. 0° 01' W., bet. secs. 35 and 36,
	Over rough mountainous land thru scattering low under-growth; desc. 90 ft. over N. slope.
9.00	Draw, drains S. 80° E., asc. 190 ft. over SE. slope.
20.60	Spur ridge, bears S. 80° E., and N. 80° W., desc. 120 ft. over broken NE. slope.
32.60	Draw, drains N. 80° E., continue over rolling land.
36.70	Spur, slopes S. 80° E.
37.40	Draw, drains S. 60° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor.; with brass cap mkd.
	$\frac{1}{4}$ S35 S36 1936
	Deposit broken glass at base of post.
43.20	Spur, slopes NE., desc. 140 ft. over broken N. slope.
48.80	Draw, drains N. 80° E.
52.40	Spur, slopes N. 70° E.
57.80	Draw, drains S. 80° E., asc. 110 ft. over rocky S. slope.
62.60	Spur, slopes N. 60° E., desc. 110 ft. over broken NE. slope.
74.10	Small draw, drains N. 60° E., continue over broken E. slope.
79.00	Small spur from SW., slopes E., desc. N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to underlying rock, with a basalt rock, 4x6x6 ins., mkd. X, deposited at the base, and in a large mound of stone to top of post, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.
	T13N R31½E S26 S25
	S35 S36 1936
	Land, mountainous.
	Soil, shallow coarse rocky loam, 3rd rate.