

SUBDIVISION OF T. 13 N., R. 31 $\frac{1}{2}$  E.

## Chains

of stone, 3 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, broken hilly.

Soil, coarse gravelly to rocky loam, 3rd rate.

Undergrowth, shadscale, greasewood.

No timber.

Grazing, fair to good.

N. 89° 50' E., on a random line, bet. secs. 1 and 12,

40.00

Set temp.  $\frac{1}{4}$  sec. cor.,

80.04

Intersect the E. bdy. of Tp., 5 lks. S. of the cor. of secs. 1 and 12, which is an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of T. 13 N., R. 32 E., surveyed under this group.

Thence

S. 89° 48' W., on true line, bet. secs. 1 and 12,

Over rolling mountainous land thru medium dense low undergrowth.

Asc. along a NE. slope.

2.40

Spur, slopes N. 30° W., asc. 160 ft. along steep N. slope.

18.50

Spur, slopes N. 70° W., desc. 210 ft. over rocky SW. slope.

27.00

Draw, drains S. 60° W., continue along S. slope.

40.02

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S 1

$\frac{1}{4}$   
S 12

1937

48.00

Dim mine road, bears S. 70° E. and N. 70° W.

52.60

Spur, slopes SW. from N. 70° E., continue along broken N. slope.

62.60

Spur, slopes N. 70° W.

From this point,

Portal of mine tunnel bears N. 52  $\frac{3}{4}$ ° E., 2.15 chs. dist.  
SE. cor. of frame mining building, 12x20 ft., bears N. 31° 01' E., 11.56 chs. distant.  
SW. cor. of frame blacksmith shop, 10x20 ft., bears N. 41° 50' E., 2.18 chs. distant.

Desc. 200 ft. over steep S. slope.

72.70

Head of draw, drains N. 30° W., asc. along N. slope.

80.04

The cor. of secs. 1, 2, 11, and 12.

Land, hilly.

Soil, shallow coarse rocky loam, 3rd rate.

Undergrowth, shadscale, greasewood.

No timber.

Grazing, fair to good.