|     | *****          |   |
|-----|----------------|---|
|     | Chains         | For description of instruments, determination of azimuth, and other instrumental data for the surveys in T. 14 N., R., $31\frac{1}{2}$ E., refer to the official field notes of T. 13 N., R. 32 E., surveyed under this group.  |
|     |                | EAST BOUNDARY OF T. 14 N., R. 31 E.   |
|     |                | Independent Resurvey of a portion of the W. bdy. of T. 13 N., R. 32 E., and a portion of the W. bdy. of T. 14 N., R. 32 E., superseding the surveys executed by Thomas K. Stewart, U. S. Deputy Surveyor in 1884 under Contract   |
|     |                | No. 170. This line is also an ESTABLISHMENT OF THE EAST BOUNDARY OF FRACTIONAL T. 14 N., R. $31\frac{1}{2}$ E. No trace of the original corners could be found. The new corners established hereon are at $40.00$ chain intervals counting from the cor. of Ts. 13 and 14 N., R. $31\frac{1}{2}$ E. and refer only to R. $31\frac{1}{2}$ E. |
|     |                | From the cor. of Ts. 13 and $14$ N., R. $31\frac{1}{2}$ E., which is an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the field notes of T. 13 N., R. 32 E., surveyed under this group.   |
|     |                | North, along the E. bdy. of Sec. 36.  |
|     | 23.01          | The reestablished NW. cor. of T. 13 N., R. 32 E., mkd. for the closing corner of Ts. 13 and 14 N., R. 32 E., For the description of this corner and for topographic items between the two corners, refer to the above field notes of T. 13 N., R. 32 E.   |
|     |                | Desc. 160 ft. over rolling and broken N. slope.   |
| 100 | 40.00          | Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for \( \frac{1}{4} \) sec. cor. of sec. 36 only, with brass cap mkd.  |
|     | 215,76         | s36 √   |
| 3   |                | 1937  |
|     |                | Deposit an igneous rock, 6x5x2 ins., mkd. X, at base of post.   |
|     | 43.00          | Mine road, bears E. and W.  |
|     | 48 <b>•</b> 00 | Branch road, bears N. 30° W. and S. 30° E.  |
| H 2 | 77.00          | Dry wash, 40 lks. wide, 1 ft. deep, course N. 20° W., continue over rolling NW. slope.  |
|     | 80.00          | Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground, for cor. of secs. 25 and 36 only, with brass cap mkd.  |
|     |                | T1↓N<br>R31⋛E   |
|     |                | 825 R32E  |
|     |                | S36 S31   |
|     |                | 1937  |

Deposit an igneous rock, 6x3x2 ins., mkd. X, at base of post.