

DEPENDENT RESURVEY 2ND STANDARD PARALLEL N. THRU R. 32 E.

Chains	Over gently rising foothills, thru medium dense undergrowth. Asc. 160 ft. to sec. cor.; asc. along E. slope.
41.46	The original standard $\frac{1}{4}$ sec. cor., which is an igneous rock, 6x12x18 ins., loosely set in small mound of stone and mkd. $\frac{1}{4}$ on N. face. Add AP on N. face. Slope changes to E. Thence, N.88°57'W., with continuous measurement.
42.20	Wash, drains N.
46.90	Wash drains NE. about 10 chs. to junction.
62.90	Wash drains N.80°E.
74.80	Wash drains N.70°E.
78.50	Wash drains N.70°E.
80.03	At a point 80.00 chs. in departure W. from the standard cor. of secs. 35 and 36, Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for standard cor. of secs. 34 and 35, with brass cap mkd. T11N R32E. SC S34 S35 1934 raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor. Land, rolling valley floor and gently rising foothills. Soil, sandy, rocky; 3rd rate. Undergrowth, shadscale, sage. Timber, none. Grazing, fair.
<hr/>	
	N. 88°57'W., along S. bdy. of sec. 34. Over rolling foothills, thru medium dense undergrowth. Asc. 365 ft. to $\frac{1}{4}$ sec. cor; asc. over E. slope.
1.86	The original standard cor. of secs. 35 and 36, which is an igneous rock, 4x10x18 ins., loosely set in small mound of stone and mkd. 4 notches on W. edge and 2 notches on E. edge. Add AP on N. face. Thence, N. 89°17'W., with continuous measurement.
17.80	Center of wash, 1 ch. wide, 6 ft. deep, drains N.60°E.
28.50	Head of wash draining NE. Slope changes to NE.
31.90	Asc. abruptly into rocky broken hills, the base of which bears N. and S.
40.00	At a point 40.00 chs. in departure W. from the standard cor. of secs. 34 and 35, Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock, and in mound of stone, 4 ft. base to top of post, for standard $\frac{1}{4}$ sec. cor. of sec. 34 only, with brass cap mkd.