

## DEPENDENT RESURVEY 2ND STANDARD PARALLEL N. THRU R. 32 E.

Chains

of draw draining N. 60° E. from W.

80.17

At a point 80.00 chs. in departure W. from the standard cor. of secs. 32 and 33,

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground to solid rock, and in mound of stone, 4 ft. base to top of post, for standard cor. of secs. 31 and 32, with brass cap mkd.

T11N R32E

SC

S31 | S32

1936

Cor. sets in head of draw draining E. about 8 chs., thence N. 60° E.

Land, rolling hills.

Soil, sandy to rocky; 3rd rate.

Undergrowth, shadscale, sage.

Timber, none.

Grazing, good.

N. 86° 16' W., along S. bdy. of sec. 31.

Over rolling hills, thru medium dense scrub undergrowth. Asc. 30 ft. to spur, over E. slope.

1.00 Spur projects N. 10° W. about 1 ch., thence N. 70° E.; desc. 25 ft. to draw.

3.20 Draw drains N. 20° W. from head S. 20° E. about 3 chs.; asc. 170 ft. to spur; along steep NE. slope.

10.60 Spur projects N. 20° W. from S.; desc. 75 ft. to draw, over NW. slope.

14.70 Draw drains N. 30° E. from head S. 30° W. about 5 chs.; asc. 200 ft. to main spur; over NE. slope.

30.40 Main spur projects N. 10° W. about 10 chs., thence NW.; desc. 130 ft. to  $\frac{1}{4}$  sec. cor.; over N. slope.

35.30 Slope changes to NW.

40.085 At a point 40.00 chs. in departure W. from the standard cor. of secs. 31 and 32.

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in mound of stone, 3 ft. base to top of post, for standard  $\frac{1}{4}$  sec. cor. of sec. 31 only, with brass cap mkd.

SC

 $\frac{1}{4}$  S31

1936

Cor. sets in head of draw draining NW. about 4 chs., thence W.

Continue same line and measurement.