SUBDIVISION OF TP. 11 N., R. 32 E.

	Chains	en e
	33.00	Small spur projects N. 2 chs. to end,; desc. over slight W. slope.
	34.10	Small draw drains N. 3 chs. to junction with draw at 28.20 ch. pt.; asc. 10 ft. over slight E. slope.
	36.20	Low spur projects N. 5 chs. to end .; desc. 25 ft. over short W. slope.
	38.00	Draw drains N.; asc. 15 ft. to the 41.60 ch. pt.; asc. over short E. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the \(\frac{1}{4} \) sec. cor., with brass cap mkd.
	101 8	1 <u>S30</u> 831
		1936
		Deposit broken glass at base of post.
		Continue over rolling hills.
	41.60	Low spur projects N.; desc. 20 ft. over W. slope.
	44.80	Junction of draws draining N.10°E. from S.30°E. and S.30°W.; asc. 20 ft. over E. slope.
	49.60	Center of wide flat spur projecting N.; desc. 15 ft. over W. slope.
	55.90	Center of draw 3 chs. wide, draining N.20°E.; asc. 130 ft. to the 77.80 ch. pt.; asc. over NE. slope.
	67.80	Head of draw draining NE.; continue ascent over steep E. slope.
	74.70	Top of spur projecting N. 2 chs., thence N.30°E. from main ridge S.; continue along N. slope.
*-	77.80	Top of ridge bearing NW. and SE.; desc. 100 ft. to closing cor.; desc. along S. slope.
	84.17	Intersect the W. bdy. of the Tp.
•		Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 30 and 31, Tp. 11 N. R. 32 E., with brass cap. mkd.
- 51	4	, Tiin
		TLIN
		S36 S30 C
		R31E R32E
200		1936
		Deposit broken glass at base of post.
		From point of intersection, the \(\frac{1}{4}\) sec. cor. of sec. 36, Tp. 11 N., R. 31 E., bears South, 18.56 chs. dist.
	* .	Land, rolling hills. Soil, sandy to rocky; 3rd rate. Undergrowth, shadscale, sage.
The second second		Timber, none. Grazing, good.
1	5	