

357

-56-

SUBDIVISION OF TP. 11 N., R. 32 E.

Chains	ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S\ 5 \mid S\ 4 \\ 1936 \end{array}$
	Deposit an igneous rock, 4x5x12 ins., mkd. with a cross (X), at base of post.
	Continue over slight NE. slope.
68.15	Intersect N. bdy. of Tp.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. of secs. 4 and 5, Tp. 11 N., R. 32 E., with brass cap mkd.
	$\begin{array}{c} T12N\ R32E \\ S33 \\ S\ 5 \mid S\ 4 \\ T11N \\ CC \\ 1936 \end{array}$
	raise a mound of stone, 4 ft. base, $3\frac{1}{2}$ ft. high, S. of cor.
	From point of intersection, the cor. of secs. 32 and 33, Tp. 12 N., R. 32 E., an iron post, 2 ins. diam., mkd. and witnessed as described in the official record, bears West, 4.00 chs. dist.
	Land, slight NE. slope. Soil, sandy; 3rd rate. Undergrowth, sage. Timber, none. Grazing, poor.
	From the cor. of secs. 29, 30, 31, and 32, heretofore described.
	N.0°03'W., bet. secs. 29 and 30.
	Over rough broken hills, thru scattering scrub undergrowth. Asc. 220 ft. to 25.00 ch. pt.; asc. over SW. slope.
.30	Draw drains N.60°W. from N.80°E. Road from Nevada Rand Mine follows course of draw to junction with Rawhide - Rand road.
6.99	From this point: The SE. cor. of an ore bin bears N.77°05'W., 88 lks. dist. The center of the main shaft of the Nevada Rand Mine bears N.0°58'E., 78 lks. dist. The NW. cor. of frame building bears N.41°15'E., 79 lks. dist.
11.30	Head of draw draining W.; asc. SW. slope.
15.88	Spur projects S.80°W. from E. From this point: