_		
	Chains 7.30	Draw drains N.30°W. from S.20°E.; asc. 50 ft. over NE. slope.
	13.40	Low saddle in spur projecting N.; desc. 120 ft. along N. slope.
	19.20	Draw drains S.60°W. from head 3 chs. N.70°E.; asc. 40 ft. along S. slope.
	24.60	Spur projects S.70°W. from N.70°E.; desc. 170 ft. over SW. slope, to 37.90 ch. pt.
		Head of draw draining S.70°W.
	34.10	Spur projects S.70°W. about 5 chs. to end.
	37.90	Head of shallow draw draining N.80°W. about 5 chs. to junction with main draw; desc. over steep W. slope; desc. 125 ft. to draw.
	40.00.	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top of post, for the 4 sec. cor., with brass cap mkd.
-	İ	1 S19 4 S30
	ns.	1936
		Continue over rolling hills; over W. slope.
	किं • 50	Draw drains N.20°W. from S.; asc. 140 ft. over steep E. slope.
	49.80	Main spur projects N. about 8 chs. to end, from S.; desc. 250 ft. to 75.30 ch. pt.; desc. over NW. slope.
	54.30	Rocky pt. on spur projecting N. 70° W; continue descent over SW. slope.
	64.30	Main draw drains, N. about 4 chs. into canyon floor bearing NE., from S.
	69.20	Draw drains N.30°E. about 2 chs. to junction. Road from Nevada Rand Mine follows course of draw to junction with Rawhide - Rand road which follows course of canyon.
	75.30	Edge of canyon bears N.60°E. and S.60°W.; asc. 30 ft. to closing cor.; asc. along S. slope.
	77.50	Main road bears N.60°E. to Rawhide, Nevada and Deadhorse Well, and S.60°W. to Rand, Nevada; asc. along S. slope.
	· 79.00 84.11	Draw, drains S. 60°. E. Intersect W. bdy. of Tp.
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. of secs. 19 and 30, Tp. 11 N., R. 32 E., with brass cap mkd.
	. 3. 	TilN S25 S30 C
		R31E R32E
		1936
		of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, E. of cor.
	P	From point of intersection, the $\frac{1}{4}$ sec. cor. of sec. 25, Tp. 11 N., R 31 E., bears South, 18.68 chs. dist.