	Chains 43.10	Spur projects N.30°E. from S.30°W.; desc. 20 ft.
	48.50	Wash drains N.40°E.; asc. 85 ft. to sec. cor.
	56.40	Wash drains N.60°E. to junction.
	63.60	Wash drains NE. to junction.
	69.30	Wash drains N.70°E.
	80.08	The cor. of secs. 7, 8, 17, and 18.
		Land, rolling. Soil, sandy to rocky; 3rd rate. Undergrowth, shadscale, sage. Timber, none. Grazing, fair.
		West, on true line bet. secs. 7 and 18.
		Over SE. slope, thru medium dense undergrowth. Asc. 250 ft. to 34.80 ch. pt.
	30.40	Wash drains NE.
	34.80	Low spur projects N.60°E.; asc. 145 ft. to closing cor.; asc. along NE. slope.
	37.50	Wash drains N.60°E. from W.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground and in a mound of stone, 5 ft. base, to top of post, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
4:	316-77	½ S 7 4 S18
		1936
	STORES.	Continue over NE. slope.
	42.00	Junction of washes draining E. from S.70°W. and from N.80°W.
1	47.20	Wash drains N.30°W.
	68.30	Wash drains NE.
	73.40	Dry channel drains NE.
*	83.87	Intersect W. bdy. of Tp.
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing.cor. of secs. 7 and 18, Tp. 11 N., R. 32 E., with brass cap mkd.
		Tiln S13 S18 C R31E R32E 1936 Deposit an igneous rock, 3x x ins., mkd. with a
		cross (X), at base of post.