	Chains 23.60	Wash drains N.30°W.; asc. 45 ft. over SW. slope.
	33.70	Spur projects N.40°W.; desc. 50 ft. over NE. slope.
	39.30	Head of draw draining N.60°W.; asc. 100 ft. to 46.40 ch. pt.; over SW. slope.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) in solid rock, and in a mound of stone, 5 ft. base, to top of post, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	. ,	
6		s 6   s.5 1936
		Continue over SW. slope.
	46.40	Spur projects N.20°W.; desc. 120 ft. over NE. slope.
	52.10	Head of draw draining S.60°E.; desc. 35 ft. over NE. slope
	56.50	Spur projects E.; desc. 110 ft. to closing cor.; over N. slope.
	68.28	Intersect N. bdy. of Tp.
	, · ·	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. of secs. 5 and 6, Tp. 11 N., R. 32 E., with brass cap mkd.
		Tien Rice
		- S32 S 6 S 5
4		T11N CC 1936
		Deposit broken glass at base of post.
	e e	From point of intersection, the cor. of secs. 31 and 32, Tp. 12 N., R. 32 E., an iron post, 2 ins. diam., mkd. and witnessed as described in the official record, bears West, 3.92 chs. dist.
+ **	. ^	Land, rolling hills. Soil, sandy to rocky; 3rd rate. Undergrowth, sage. Timber, none. Grazing, fair.
,	- P	
		ESTABLISHMENT OF THE \( \frac{1}{4}\) SEC. CORS. ON N. BDY. OF TP. 11 N., R. 32 E.
		QUARTER SEC. COR. ON N. BDY. OF SEC. 1.  From the \(\frac{1}{4}\) sec. cor. of sec. 36, Tp. 12 N., R. 32 E.
	is.	East, 3.70 chs. dist.
	Telephone to	To a point mid-way bet. the closing cor. of Tps. 11 N., Rs. 32 and 33 E., and the closing cor. of secs. 1 and 2.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the 4 sec. cor. of sec. 1 only, with brass cap mkd.