

INDEPENDENT RESURVEY EAST BOUNDARY OF T. 13 N., R. 31½ E.

Chains

INDEPENDENT RESURVEY of the
EAST BOUNDARY OF T. 13 N., R. 31½ E.

Superseding the survey of the West bdy. of T. 13 N., R. 32 E. executed by T.K. Stewart, U.S. Deputy Surveyor in 1884 under Contract No. 170.

The cor. of Tps. 12 and 13 N., R. 31½ E. is an iron post, 3 ins. diam., firmly set, mkd. and wit. as described in the field notes of the survey of T. 12 N., R. 31½ E., executed under this same group.

Thence

North, along the E. bdy. of Sec. 36, on blank line,
(For topography and detailed record of this portion of the E. bdy. of Sec. 36, refer to the field notes of the survey of T. 12 N., R. 32 E., executed under this same group.)

- 22.62 The closing cor. of Ts. 12 and 13 N., R. 32 E., which is an iron post, 3 ins. diam., firmly set, mkd. and wit. as described in the above field notes of the survey of T. 12 N., R. 32 E.
- 28.10 Draw, drains N. 70° E.; desc. 30 ft. over rolling foothill.
- 31.10 Wash, course N. 70° E.; desc. over broken land.
- 36:00 Spur, slopes N. 70° E.; continue over broken land.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the ¼ sec. cor. for sec. 36 only, with brass cap mkd.
- ¼ S36 |
1936
- raise a mound
of stone, 3 ft. base, 2 ft. high, W. of cor.
- 45.70 Draw, drains E.; asc. short abrupt slope.
- 47.40 Spur, slopes E.; desc. 30 ft. over N. slope.
- 57.40 Draw, drains N. 80° E.; asc. 40 ft. over a S. slope.
- 62.20 Top of ascent, bears E. and W.; desc. 80 ft. over a broken N. slope.
- 67.90 Draw, drains E.; asc. 30 ft. over broken land.
- 70.90 S. bank of wash, course S. 30° E.
- 79.00 N. bank of wash, course S. 30° E.; asc. gentle S. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 25 and 36 only, with brass cap mkd.

T13N
R31½E | R32E
S 25 |
S 36 | S 31
1936