

INDEPENDENT RESURVEY EAST BOUNDARY of T. 13 N., R. 31½ E.

Chains

- North, along the E. bdy. of Sec. 1,
 Desc. 160 ft. over rolling mountainous land, on a NE. slope, thru scattering undergrowth.
- 5.80 Low spur, slopes N.; continue along top of spur.
- 14.20 Draw, drains NE.; asc. slightly over a SE. slope.
- 21.30 Spur, slopes N. 20° E.; desc. 80 ft. over a broken NW. slope.
- 22.53 The closing cor. for secs. 6 and 7, hereinafter described.
- 25.30 Draw, drains NW.; asc. slightly along a W. slope.
- 31.00 Spur, slopes N. 30° E.; desc. 190 ft. over NE. slope.
- 39.90 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for witness ¼ sec. cor. of sec. 1 only, with brass cap mkd.

WC
 ¼ S1
 1937

of stone, 2 ft. base, 1½ ft. high, W. of cor. raise a mound

- 40.00 Point for ¼ sec. cor. of sec. 1 falls in road bearing N. 10° E. and S. 10° W. where is impracticable to set a permanent monument.
- 50.80 Shallow wash, course N. 10° E.
- 67.40 Draw, drains N. 80° E.; asc. 50 ft. over a S. slope.
- 72.70 Spur, slopes S. 80° E.; desc. 20 ft. over a NE. slope.
- 74.80 Draw, drains S. 60° E.; asc. 30 ft. over a SW. slope.
- 76.40 Spur, slopes S. 70° E.; desc. 40 ft. along an E. slope.
- 79.67 Set an iron post, 3 ft. long, 3 ins. diam., 18 ins. in the ground, to bedrock, with a granite stone, 4x4x3 ins., mkd X, deposited at the base, and in a mound of stone to top, for the cor. of Tps. 13 and 14 N., R. 31½ E.; with brass cap mkd.

T14N
 R31½E | T13N
 S 36 | S 6
 S 1 |
 T13N | R32E

1937

Land, rolling and broken mountainous.
 Soil, rocky clay, 3rd rate.
 Timber, none; undergrowth, sagebrush, greasewood, and shadscale.
 Grazing, fair to poor.