

INDEPENDENT RESURVEY OF PORTION OF E. Bdy. of T. 14 N., R. 31 $\frac{1}{2}$ E.

392

Chains	From the cor. of Tps. 13 and 14 N., R. 31$\frac{1}{2}$E., continuing independent resurvey. North, along the W. bdy. of sec. 6. Desc. 90 ft. over rolling mountainous land, along an E. slope, thru scattering undergrowth. 8.40 Spur, slopes N. 20° E. 11.70 Draw, drains N. 30° E. 14.00 Spur, slopes E. 19.30 Spur, slopes N. 60° E.; over broken land. 23.01 Intersect the N. bdy. of T. 13 N., R. 32 E., at the closing cor. bet. Tps. 13 and 14 N., R. 32 E., hereinafter described. Land, rolling mountainous. Soil, rocky, 3d and 4th rate. Timber, none; undergrowth, sagebrush and greasewood. Grazing, poor.
	INDEPENDENT RESURVEY NORTH BOUNDARY, T. 13 N., R. 32 E. Superseding the survey executed by T. K. Stewart, U. S. Deputy Surveyor in 1884, under Contract No. 170, Nevada. From the cor. of Tps. 13 and 14 N., Rs. 32 and 33 E., hereinbefore described. West, on true line, bet. secs. 1 and 36. Desc. 10 ft. over mountainous land, on a NW. slope, thru scattering undergrowth. 1.30 Wash, course N.; asc. 70 ft. over broken land. 7.90 Spur, slopes NE.; desc. 50 ft. over a SW. slope. 12.10 Wash, course SE.; asc. 30 ft. over broken land. 18.10 Spur, slopes S.; desc. 40 ft. abruptly. 21.00 Wash, course N.; asc. 40 ft. along a S. slope. 26.40 Spur, slopes S.; asc. 30 ft. on top of spur. 32.10 Leave top of spur, bears N. and S.; desc. 30 ft. abruptly. 34.90 Wash, course SW.; road, bears NE. and SW.; desc. slightly over broken land. 40.00 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with a granite stone, 4x3x3 mkd. X, deposited at base, and in amount of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd. S36 $\frac{1}{4}$ S 1 1937 41.70 Spur, slopes S.; desc. 20 ft. abruptly. 43.60 Draw, drains SE.; asc. 220 ft. over a SE. slope.