

60
439

SUBDIVISION, T. 13 N., R. 32 E.

Chains	
66.20	Wash, 50 lks. wide, course E., into Wash, at 51.60 chs.
78.22	Intersect the W. bdy. of the Tp. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. for secs. 18 and 19, with brass cap mkd.
	<p>raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.</p> <p>From this point the $\frac{1}{4}$ sec. cor. for sec. 13, T. 13 N., R. $31\frac{1}{2}$ E., hereinbefore described, bears N. 17.50 chs. dist.</p> <p>Land, rolling. Soil, rocky, sandy clay, 3d rate. Timber, none; undergrowth, buttonbrush, mountain rush, sagebrush, shadscale and greenbrush. Grazing, poor to fair.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20. N. $0^{\circ} 03'$ W., bet. secs. 17 and 18.</p> <p>Desc. slightly over rolling land, along a NW. slope, thru scattering undergrowth.</p>
2.90	Wash, 80 lks. wide, course S. 70° E.; asc. slightly along a SE. slope.
11.00	Wash, course E.; road, bears N. 60° E. and S. 60° W.; asc. 130 ft. over an even SE. slope.
38.20	Leave SE. slope, asc. 70 ft. abruptly.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground to bedrock, with a granite stone, 5x5x4 ins. mkd. X, deposited at base, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
44.00	Ridge, bears E. and W.; desc. 160 ft. over a broken N. slope.
59.80	Draw, drains E.; asc. 90 ft. along a broken E. slope.
66.00	Knoll.
68.60	Draw, drains S. 60° E.
71.80	Spur, slopes S. 60° E.; desc. slightly over broken land.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. of secs. 7, 8, 17, and 18, with brass cap mkd.