


SUBDIVISION OF T. 12 N., R. 32 E.

Chains 29.00	Main spur, projects S. 70° E.; continue along S. slope of main spur.
31.00	Head of draw, drains S. 60° E.
38.00	Low spur, projects SE. 5 chs. to end.
40.00	Set an iron post, 3 ft. long, 1 in. diam., on solid rock and supported in a mound of stone 5 ft. base to top of post, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ $\frac{S18}{S19}$ 1936
	This cor. is situated in a draw draining S. 70° E.; asc. over steep E. slope.
44.90	Spur, projects S. 20° E.; continue ascent over SE. slope.
49.30	Spur, projects S.; desc. 15 ft. over a W. slope.
52.50	Head of draw, drains S.; asc. 45 ft. over steep E. slope.
54.60	Spur, projects S. about 10 chs. to end; desc. 20 ft. along S. slope.
58.60	Draw, drains SE.; asc. 150 ft. over steep E. slope to 66.60 ch. pt.
61.50	Spur, projects SE. about 8 chs. to end; continue along S. slope.
63.50	Head of draw, drains SE.
66.60	Spur, projects S.; desc. 95 ft. along S. slope to 74.10 ch. pt.
71.70	Slope changes to an abrupt W. slope.
74.10	Junction of draws draining from N. and NW., drains S.; asc. 55 ft. over an abrupt E. slope.
78.00	Divide, bears N. 20° E. and S. 20° W.; desc. gentle SW. slope.
79.26	Intersect the W. bdy. of the Tp.

At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone 3 ft. base to top of post, for the closing cor. of secs. 18 and 19, T. 12 N., R. 32 E., with brass cap mkd.



From this point the $\frac{1}{4}$ sec. cor. of sec. 13, T. 12 N., R. 31 $\frac{1}{2}$ E., heretofore described, bears North, 19.24 chs. dist.

Land, rolling hills.
Soil, rocky to gravelly; 3rd rate.
Undergrowth, sagebrush.
Timber, none.
Grazing, fair.