

SUBDIVISION OF T. 12 N., R. 32 E.

Chains	bottom of wash.
80.00	The cor. of secs. 5, 6, 7, and 8. Land, E. $\frac{1}{2}$ mile, rolling; W. $\frac{1}{2}$ mile, rolling foothills. Soil, sandy to rocky; 3rd rate. Undergrowth, shadscale. Timber, none. Grazing, fair.
	West, on true line bet. secs. 6 and 7. Over rolling foothills; through medium dense undergrowth; asc. over a general E. slope.
9.00	Dry wash, drains S. 80° E. from N. 30° W.
28.00	Dry wash, drains S. 30° E.
40.00	On E. slope 130 ft. above sec. cor., Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{r} S6 \\ \frac{1}{4} \text{ ---} \\ S7 \\ 1936 \end{array}$ Deposit broken glass at base of post. Asc. 140 ft. over NE. slope.
57.30	Low spur, projects N. 5 chs. to end; desc. 20 ft. over W. slope.
65.30	Dry wash, drains N. 30° E.; asc. 130 ft. over broken E. slope.
78.90	Intersect the W. bdy. of the Tp. At the point of intersection, Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone 5 ft. base to top of post, for the closing cor. of secs. 6 and 7, T. 12 N., R. 32 E., with brass cap mkd. $\begin{array}{r} T12N \\ R32E \\ R31\frac{1}{2}E \quad S6 \quad C \\ S1 \quad S7 \quad C \\ 1936 \end{array}$ From this point, the $\frac{1}{4}$ sec. cor. of sec. 1, T. 12 N., R. 31 $\frac{1}{2}$ E., heretofore described, bears North, 19.14 chs. dist. Land, rolling foothills. Soil, gravelly to rocky; 3rd rate. Grazing, poor. Undergrowth, greasewood. Timber, fair.