SURVEY OF THE NORTH BOUNDARY OF T. 9 S., R. 68 E.

Chains	
	Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, and in a mound of stone to top, for the cor. of secs. 5, 6, 31, and 32, with the brass cap mkd.
	T8½SR68E S31 | S32 S6 | S5 T9S 1934
	Land, rolling. Soil, sandy to gravelly; 3rd rate. Undergrowth, black brush, creosote, mountain rush, cacti. Native grasses. No timber.
	West, bet. secs. 6 and 31, on a transit line describing the tangent, which bears S. 89° 56.7' W.
	Over rolling lands, through scattering undergrowth; descend 245 ft. over a general SW. slope to the 80.00 ch. point.
15.90	Draw, drains S.
20.30	Spur, projects SW.
38.00	Wash, drains S. 10° W.
40.00	N. 23 lks. from the tangent,
	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, and in a mound of stone to top, for the ¼ sec.cor., with the brass cap mkd.
	¼ S31/S6 1934
	No suitable accessory available.
41.40	Spur, projects S. 10° W.
54.35	Wash, drains S. 20° W.
67.90	Spur, projects SW.
75.75	Wash, drains NW. about 4.00 chs. to wash draining SW.
77.36	Spur, projects N. about 1½ chs.
78.80	Wash, drains SW.
80.00	N. 27 lks. from the tangent,
	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone to top of post, for the cor. of lots 8 and 9 of sec. 31, and lots 4 and 5 of sec. 6, with the brass cap mkd.