

SUBDIVISION OF T. 9 S., R. 68 E.

Chains

80.00

Set an iron post, 3 ft. long, 2 in. diam., 30 ins. in the ground, for the cor. of lots 7 and 8, sec. 19, and lots 1 and 2, sec. 30, with brass cap mkd.

T9SR68E

S19

7	8
2	1

S30

1934

raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

90.20

Low spur, projects S. 10° W. from NE.; desc. 25 ft.

96.08

Intersect the E. bdy. of T. 9 S., R. 67 E.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. of secs. 19 and 30, with brass cap mkd.

T9S

R67E

R68E

S25

S19	C
-----	---

S30	C
-----	---

1934

deposit a lime-stone, 4x4x3 ins., mkd. with a cross (X) at base of post.

From point of intersection the ¼ sec. cor. of sec. 25, T. 9 S., R. 67 E., hereinafter described, bears N. 0° 03' E., 22.95 chs. dist.

From the same point the cor. of secs. 25 and 36, T. 9 S. R. 67 E., hereinafter described, bears S. 0° 03' W., 17.02 chs. dist.

Land, rolling.

Soil, gravelly to rocky; 4th rate.

Undergrowth, blackbrush, sagebrush, creosote, and cacti.

Native grasses.

No timber.

From the cor. of secs. 19, 20, 29, and 30. N. 0° 03' W., bet. secs. 19 and 20.

Over mountainous land, through medium dense undergrowth; desc. 40 ft.

2.70

Wash, drains N. 20° W.; asc. 140 ft. on a steep S. slope.

11.00

Top of ascent, bears E. and W.; desc. 175 ft. on a N. slope.

32.30

Wash, drains S. 60° W.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, in a mound of stone to top, for ¼ sec. cor. with brass cap mkd.