

1174

SURVEY OF THE RANGE LINE THROUGH T. 9 S., BETWEEN RS. 69 AND 70 E.

Chains

Deposit a granite rock 3x3x5 ins., mkd. with cross (X), at base of post.

80.00

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground for cor. of secs. 1, 6, 31, and 36, Tps. 8½ and 9 S., Rs. 69 and 70 E., with brass cap mkd.

T8½S
R69E R70E
S36 S31
S1 S6
T9S
1934

Deposit a limestone, 3x4x4 ins., mkd. with cross (X), at base of post.

No suitable witnesses or bearings available at this cor.

Land, sandy and gravelly loam; 3rd rate.
Undergrowth, creosote, cacti, blackbrush, buckbrush.
No timber.

NORTH BOUNDARY T. 9 S., R. 69 E.

Beginning at the cor. of Tps. 8½ and 9 S., Rs. 69 and 70 E., I turn an angle of 89°55' to the right from a flag point left of the range line S. and run.

S. 89°55' W. on a random line, making proper offsets to the north from the tangent to the parallel at intervals of 40.00 chs., setting temp. ¼ sec. and sec. cors. along the line bet. Tps. 8½ and 9 S., R. 69 E. At 477.58 chs., the parallel intersects a N. and S. line 126 lks. S. of the cor. of Tps. 8½ and 9 S., Rs. 68 and 69 E., which is an iron post, 3 ins. diam., mkd. and witnessed as described in Book "A" this group. The correction is 21.0 lks. N. per mile, counting from the point of beginning.

Thence

S. 89°56' E., on true line, bet. secs. 6 and 31.

Over rolling and broken land, through medium dense undergrowth.

0.90

Small draw, drains S.; asc. 40 ft. over a W. slope.

3.70

Small spur, projects S.; desc. 40 ft. over a broken E. slope.

11.60

Road, bears NE. and SW.

15.60

Dry wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.

37.58

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, for ¼ sec. cor., with brass cap mkd.

S31
¼
S6
1934

(X) Deposit an andesite rock 4x6x8 ins., mkd. with (X) cross, at base of post.